

THEATRE

SPARK 575



- A new followspot with a high quality illumination.
- Perfect light distribution in a short/medium throw unit.
- New compact design and new shape for easy handling.
- Standard equipped with dimmer/black out and iris.
- Optionally available a 5 filters colour changer.



Technical Data

Power supply	230V 50Hz (60Hz to order).	Power consumption	800VA at 230V.
Lamp	MSR 575, MSR 575/2, HSR 575/60, HSR 575/72, HSD 575, MSD 575 discharge lamp. Colour Temperature 5600K. Socket GX 9.5, life 2000 hours (manufacturer ratings).	Colours	Optional colour changer for 5 dichroic filters or gel.
Strobe-shutter	Blackout shutter provided.	Cooling	Forced cooling via low noise axial fan.
Housing	Extruded aluminium and steel plate. Metal parts have epoxy powder paint finish. Easy access to lamp and main components. Protection: IP20.	Operating parameters	Projector may be tilted +55°/-40° from the horizontal.
Dimmer	Variable dimmer from 0% to 100%.	Gobo holder	Optional gobo holder for 66mm diameter M-size gobo.
Beam divergence	10° to 20°.	Dimensions	910mm L x 320mm W x 420mm H (included bracket).
Weight	Weight 26kg.	Iris	Interchangeable iris included.
Reference norm	CE.	Notes	Spark 575 order codes: 1309PF Spark 575 819PF optional gobo holder 1309CC optional colour changer 253PFB Blue dichroic colour filter 253PFF Magenta dichroic colour filter 253PFG Green dichroic colour filter 253PFR Red dichroic colour filter

253PFY Yellow dichroic colour filter